

System 6


Quickfit-Expando

Expanding dowels

- Available in Ø5mm, Ø8mm and Ø10mm for panel-to-panel, panel-to-hollow profile and back-to-back applications
- Suitable for applications with all Titus Ø20 and/or Ø25mm Expando-6 housings
- 'Klix' locking feature provides a strong, vibration proof connection
- Depth stop collar for accurate insertion




DU PONT
HANDEL EN MAATWERK



Technical and mounting details


Dowel Ø5 and Ø8



5000 Pcs

Made of zinc, plastic


Ø5 x 7.5 back-to-back applications



5000 Pcs

Made of zinc, plastic

Ø8 x thru panel-to-frame applications




















4000 Pcs

Made of zinc, plastic


D2	Drilling diameter for dowel thread	Item number	Color		
			Dark grey	Black	Zinc
5	5	06408 →	880		
8	8	06410 →	880		
		06479 →	880		
		06477 →	835		

System 6 Quickfit-Expando Dowels

- Available in various Ø3mm and/or Ø5mm thread forms for screw-in, knock-in and/or 'spiked' hole applications
- Suitable for applications with all Titus Ø20mm and/or Ø25mm Expando-6 housings
- 'Klix' locking feature provides a strong, vibration proof connection
- Dowels feature an integral skirt which acts as a positive stop during insertion

 Technical and mounting details		C	Drilling length for dowel thread	Item number	Material	
					Zinc	Zinc plated
Dowel     2000 Pcs Made of zinc or steel			9	06401 →	885	
			8	06402 →	885	883
			11.5	06406 →	885	883
Ø5 x 11 knock-in     2000 Pcs Made of zinc				06403 →	885	
M4 x 7     4500 Pcs Made of steel				06405 →	883	
Ø3 x 11.5     12500 Pcs Made of steel				06495 →	883	

 **Sleeves**
Made of brass → see page 1.53

 **Inserts**
Made of plastic → see page 1.60